



MTS VIGILANT

TECHNICAL SPECIFICATIONS

GENERAL

Type	Shoalbuster 3009
Classification	Germanischer Lloyd: 100 A5 (Tug) MC - USL 2A
MMSI	376656000
IMO number	9533969
Year built	2008 - Damen Shipyard, NL
Flag	St Vincent and The Grenadines
Port of registry	Kingstown
Call sign	J8135266

DIMENSIONS

Length	30,08 m
Breadth overall	9,10 m
Minimum draft	2,90 m
Operational Draft	3,00 m
Maximum draft	3,20 m
Minimum air draft	10,30 m
Maximum air draft	16,00 m
Gross tonnage	309 t
Net tonnage	92 t

TANK CAPACITY

Fuel oil	174,90 m ³
Fresh water	40,90 m ³
Lubrication oil	7,30 m ³
Hydraulic oil	3,10 m ³
Dirty oil	4,30 m ³
Sewage	3,30 m ³
Bilge water	4,30 m ³

PERFORMANCE

BollardPull	50 t
Maximum speed	11,00 knots
Economic speed	9,00 knots
Horse power	3300

PROPULSION SYSTEM

Main engines	2x Caterpillar 3512B TA/C, 12 cyl, 1600 rpm
Total power	2.460 kW / 3300 bhp
Propulsion	2x Promarine fixed pitch propeller
Bowthruster	250 bhp, hydraulic driven

DECK CRANE

Type	Heila HLRM 170-3SL
Capacity	5,30 T @ 18,03 m

DECK EQUIPMENT

Free deckspace	65,0 m ²
Deck strength	15,0 t/m ²
Tugger winch	8 t
Pushbow	Full length rubber fendered

AUXILIARY EQUIPMENT

Main generator sets	2x Caterpillar C4.4 TA
Fuel oil transfer pump	VWSI 8020,50 m/h @4,8 bar
Fresh water transfer pump	VWSI 8020,50 m/h @4,8 bar
Fresh water maker	HEM 4 m ³ every 24h
Air compressor	ABAC B5900 B
Powerpack	CAT C-18 TA

ACCOMMODATION

Persons	7
Single cabin	3
Double cabin	2
Air conditioned	Yes

TOWING EN ANCHOR HANDLING

Towing winch	Ridderinkhof Waterfall 50 t / 100 t (pull/hold) 750 m x 44 mm
Anchor Handling Winch	100 t / 100 t (pull/hold) 600 m x 40 mm
Towing pins	3-in row + Shark Jaw Fork
Stern roller	SWL 100t



MTS VIGILANT

